

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1 (Currently Amended). A tool holder for a hand supported impacting machine, which tool holder is suitable for receiving a tool having a shank portion on which is formed a retaining collar, the tool holder comprising:

a tubular main body for receiving the tool, and

an elongated locking element moveably pivotably mounted at a pivot point on an exterior surface of ~~with respect to~~ the main body, the locking element including a forward portion including an engaging portion located forward of the pivot point, the engaging portion pivotably moveable between a radially inner locked position, in which the engaging portion is engageable with the retaining collar of the tool, and a radially outer unlocked position, which enables a tool to be inserted into or removed from the main body; and

a manually actuatable sleeve which is mounted around the main body so as to be moveable between a first position in which the engaging portion of the locking element is held in the locked position and a second position in which the engaging portion of the locking element is moveable to the unlocked position.

2 (Original). A tool holder according to claim 1 wherein the manually actuatable sleeve is axially slideably mounted along the main body.

3.(Original). A tool holder according to claim1 and further comprising:

a retaining ring axially slideably mounted with respect to the main body; and

a spring member that axially biases the retaining ring into engagement with the locking element so as to bias the locking element engaging portion into the locked position.

4 (Original). A tool holder according to claim 1 and further comprising a spring member that biases the manually actuatable sleeve into the first position.

5 (Original). A tool holder according to claim 1 and further comprising a second locking element.

6 (Original). A tool holder according to claim 3 wherein the retaining ring is located rearwardly of the locking element and the spring member axially biases the retaining ring in the forwards direction.

7 (Original). A tool holder according to claim 3 wherein the axial movement of the retaining ring is independent of the movement of the manually actuatable sleeve.

8 (Cancelled).

9 (Currently Amended). A tool holder according to claim [[8]] 1 wherein the main body defines a recess and the locking element includes a rearward portion bearing a radially inwardly projecting portion engageable with the recess on the main body so as to facilitate pivoting of the locking element.

10 (Currently Amended). A tool holder according to claim [[9]] 1 wherein the main body includes a radially outward projection and the locking element includes a radially inwardly facing recess, and the locking element recess is engageable with the projection on the main body so as to facilitate pivoting of the locking element.

11 (Cancelled).

12 (Currently Amended). A tool holder according to claim [[8]] 1 wherein the locking element includes a radially outward portion and the manually actuatable sleeve includes a radially inward locking member and when the manually actuatable sleeve is in the first position then the locking member is engageable with the radially outward portion of

the locking element to hold the engaging portion of the locking element in the locked position.

13 (Original). A tool holder according to claim 12 wherein the locking element includes a reduced external diameter portion and when the manually actuatable sleeve is in the second position then the locking member is located radially outward of the reduced external diameter portion of the locking element.

14 (Original). A tool holder according to claim 12 wherein when the manually actuatable sleeve is in the second position, then the locking member is located one of axially forward and axially rearward of the locking element.

15 (Original). tool holder according to claim 3 wherein the locking element includes a first end and is pivotally mounted on the main body about the first end so that the engaging portion is radially movable with respect to the main body between the locked position and the unlocked position, and the retaining ring defines a recess, and the first end of the locking element is receivable in the recess so as to guide the pivoting of the locking element

16 (Original). A tool holder according to claim 5 wherein the locking element and the second locking element are pivotally mounted on the main body and, when the engaging portions are in the locked position, the locking element and second locking element together form a sleeve which surrounds the tool inserted within the main body.

17 (Currently Amended). A tool holder according to claim [[8]] 1 wherein a forward end of the locking element extends forwardly of a forward end of the main body.

18 (Original). A tool holder according to claim 17 wherein the locking element includes a rearward portion and a forward portion, the rearward portion is pivotally mounted on the main body and the engaging portion is located on the forward portion.

19 (Original). A tool holder according to claim 16 wherein the locking element and second locking element both include a resilient ring portion mounted at a forward end

of each locking element, and in the locked position of the engaging portions of the locking elements the ring portions together form a resilient nose ring.

20 (Currently Amended). A tool holder according to claim [[8]] 1 wherein the main body defines a radial through hole, and the locking element has a radially inwardly extending engaging portion extendable through the through hole.

21 (Original). A tool holder according to claim 20 wherein the through hole is axially longer than the engaging portion of the locking element.

22 (Original). A tool holder according to claim 20 and further comprising:

a retaining ring axially slideably mounted around the main body rearward of the locking element;

a spring member for forwardly biasing the retaining ring into engagement with the locking element; and

wherein the locking element is axially slideably mounted on the main body.

23 (Original). A tool holder according to claim 22 wherein the manually actuatable sleeve member includes a locking member located within the manually actuatable sleeve and in the locked position of the sleeve the locking member engages a radially outward portion of the locking element to hold the engaging portion of the locking element in the locked position, and wherein the retaining collar of a tool inserted into the main body is engageable with the locking element so as to push the locking element to a rearward position against the force exerted by the forward biased retaining ring.

24 (Currently Amended). A tool holder according to claim 23 wherein the rearward position of the locking element is rearward of the locking member, and in the rearward position of the locking element the engaging portion of the locking ~~element~~ element is moveable to the unlocked position.

25 (Original). A tool holder according to claim 22 wherein the main body includes an outer surface and the outer surface defines a recess and a slot extending axially

rearwardly from the recess, and wherein the locking element is axially slideably guided in the slot and pivotable in the recess.

26 - 32 (Cancelled).

33 (Currently Amended). A hand supported impacting machine comprising a hammering mechanism and a tool, the tool holder is suitable for receiving a tool having a shank portion including a retaining collar, and wherein the tool holder comprises:

a tubular main body for receiving the tool, and

an elongated locking element ~~moveably~~ pivotably mounted at a pivot point on an exterior surface of ~~with respect to~~ the main body, the locking element including a forward portion including an engaging portion located forward of the pivot point, the engaging portion pivotably moveable between a radially inner locked position, in which the engaging portion is engageable with the retaining collar of the tool, and a radially outer unlocked position, which enables a tool to be inserted into or removed from the main body; and

a manually actuable sleeve which is mounted around the main body so as to be moveable between a first position, in which the engaging portion of the locking element is held in the locked position, and a second position, in which the engaging portion of the locking element is moveable to the unlocked position.